



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Cover Sheet and Revision Status

版別 (Rev.)	DCC No	生效日 (Eff. Date)	變更說明 (Change Description)	發行人 (Originator)
1.0	20240018	Apr. 26, 2017	New issue	Hank Lin
2.0		Nov. 8, 2021	Revise "Chiplus reserves the right to change product or specification without notice" to "Chiplus reserves the right to change product or specification after approving by customer " Delete 5V product Corrected the minimum value of tAS and tWR from 0ns to 1.5ns	Hank Lin
3.0		Oct. 22, 2024	Corrected the minimum value of tAS and tWR from 0ns to 1.5ns	Hank Lin



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

GENERAL DESCRIPTION

The CS18FS3216W and CS16FS3216W are a 33,578,432-bit high-speed Static Random Access Memory organized as 4M(2M) words by 8(16) bits. The CS18FS3216W (CS16FS3216W) uses 8(16) common input and output lines and have an output enable pin which operates faster than address access time at read cycle, And CS16FS3216W allows that lower and upper byte access by data byte control(\overline{UB} , \overline{LB}). The device is fabricated using advanced CMOS process, 6-TR based cell technology and designed for high-speed circuit technology. It is particularly well suited for use in high-density high-speed system applications. The CS18FS3216W and CS16FS3216W are packaged in 48 TFBGA.

FEATURES

- Fast Access Time 10,15ns(Max)
- CMOS Low Power Dissipation
 - Standby (TTL) : 70mA (Max.)
 - (CMOS) : 55mA (Max.)
 - Operating : 120mA (10ns, Max.)
 - : 100mA (15ns, Max.)
- Wide range of Power Supply
 - **CSXXFS3216W**: 1.65V~3.6V Power Supply:
- TTL Compatible inputs and Outputs
- Fully Static Operation, No Clock or Refresh required
- Three State Outputs
- Data Byte Control(x16 Mode)
 - \overline{LB} : I/O₀~I/O₇, \overline{UB} : I/O₈~I/O₁₅
- Standard 48 TFBGA Package Pin Configurations
- ROHS compliant
- Operating in Commercial and Industrial Temperature range.



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W


Order Information

Density	Org.	Part Number	V _{CC} (V)	Speed		Package	Temp.
				t _{AA} (ns)	t _{OE} (ns)		
32Mb	4Mx8	CS18FS3216WHC(I)-10*	2.5~3.3	10	5	48 TFBGA	C : Commercial I : Industrial
			1.8	15	7		
	2Mx16	CS16FS3216WHC(I)-10*	2.5~3.3	10	5		
			1.8	15	7		

*means max. speed


PIN CONFIGURATIONS

6x8mm TFBGA with ball pitch 0.75mm



CS18FS3216W – (4M x 8)

Top View



CS16FS3216W – (2M x 16)


Top View




32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

FUNCTIONAL BLOCK DIAGRAM



CS18FS3216W– (4M x 8)



CS16FS3216W – (2M x 16)

Absolute Maximum Ratings*

Parameter		Symbol	Rating	Unit
Voltage on Any Pin Relative to V _{SS}		V _{in} , V _{OUT}	-0.5 to V _{CC} +0.5V	V
Voltage on V _{CC} Supply		V _{in} , V _{OUT}	-0.5 to 4.6	V
Power Dissipation		P _D	1.0	W
Storage Temperature		T _{STG}	-65 to 150	°C
Operating Temperature	Commercial	T _A	0 to 70	°C
	Industrial	T _A	-40 to 85	°C

*Stresses greater than those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operating sections of this specification is not implied.

Exposure to absolute maximum rating conditions for extended periods may affect reliability.



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Recommended DC Operating Conditions*(T_A=0 to 70°C)

Parameter	Operating V _{CC} (V)	Symbol	Min.	Typ.	Max.	Unit
Supply Voltage	2.4~3.6	V _{CC}	2.4	2.5/3.3	3.6	V
	1.65~2.2	V _{CC}	1.65	1.8	2.2	
Ground		V _{SS}	0	0	0	V
Input High Voltage	2.4~3.6	V _{IH}	2.0	-	V _{CC} +0.3	V
	1.65~2.2	V _{IH}	1.4	-	V _{CC} +0.2	
Input Low Voltage	2.4~3.6	V _{IL}	-0.3	-	0.7	V
	1.65~2.2	V _{IL}	-0.3	-	0.4	

*The above parameters are also guaranteed for industrial temperature range.

DC and Operating Characteristics*(T_A=0 to 70°C)

Parameter	Symbol	Test Conditions		Min	Max	Unit
Input Leakage Current	I _{LI}	V _{IN} =V _{SS} to V _{CC}		-2	2	uA
Output Leakage Current	I _{LO}	\overline{CS} =V _{IH} or \overline{OE} =V _{IH} or \overline{WE} =V _{IL} V _{OUT} =V _{SS} to V _{CC}		-2	2	uA
Operating Current	I _{CC}	Min.Cycle,100% Duty	10ns	-	120	mA
		\overline{CS} =V _{IL} , V _{IN} =V _{IH} or V _{IL} ,I _{OUT} = 0mA	15ns		100	
Standby Current	I _{SB}	Min. Cycle, \overline{CS} =V _{IH}		-	70	mA
	I _{SB1}	f=0MHz, \overline{CS} ≥V _{CC} -0.2V, V _{IN} ≥V _{CC} -0.2V or V _{in} ≤ 0.2V		-	55	
Output Low Voltage Level	V _{OL}	V _{CC} =3.0V, I _{OL} =8mA,(Case of Typical Vcc=3.3V)		-	0.4	V
		V _{CC} =2.4V, I _{OL} =1mA, (Case of Typical Vcc=2.5V)		-	0.4	
		V _{CC} =1.65V, I _{OL} =0.1mA,(Case of Typical Vcc=1.8V)		-	0.2	
Output High Voltage Level	V _{OH}	V _{CC} =3.0V, I _{OH} =4mA,(Case of Typical Vcc=3.3V)		2.4	-	V
		V _{CC} =2.4V, I _{OH} =1mA,(Case of Typical Vcc=2.5V)		2.4	-	
		V _{CC} =1.65V, I _{OL} =0.1mA,(Case of Typical Vcc=1.8V)		1.8	-	



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

*The above parameters are also guarantee for industrial temperature range.

Capacitance*($T_A = 25^\circ\text{C}$, $f = 1.0\text{MHz}$)


Item	Symbol	Test Conditions	TYP	Max	Unit
Input/ Output Capacitance	$C_{I/O}$	$V_{I/O}=0\text{V}$	-	10	pF
Input Capacitance	C_{IN}	$V_{IN}=0\text{V}$	-	16	pF

*Capacitance is sampled and not 100% tested.

Test Conditions*

Parameter	Value
Input/ Output Capacitance	0 to 3.0V ($V_{CC}=3.3\text{V}$)
	0 to 2.5V ($V_{CC}=2.5\text{V}$)
	0 to 1.8V ($V_{CC}=1.8\text{V}$)
Input Rise and Fall Time	1V/1ns
Input and Output Timing Reference Levels	1.5V ($V_{CC}=3.3\text{V}$)
	$1/2V_{CC}$ ($V_{CC}=1.8\text{V}$ or 2.5V)
Output Load	See Fig. 1

*The above parameters are also guaranteed for industrial temperature range.



* Including Scope and Jig Capacitance

Fig. 1




Fig. 2



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Functional Description (x8 Mode)

\overline{CS}	\overline{WE}	\overline{OE}	Mode	I/O Pin	Supply Current
H	X	X*	Not Select	High-Z	I _{SB} , I _{SB1}
L	H	H	Output Disable	High-Z	I _{CC}
L	H	L	Read	D _{OUT}	I _{CC}
L	L	X	Write	D _{IN}	I _{CC}

*X means don't care

Functional Description (x16 Mode)

\overline{CS}	\overline{WE}	\overline{OE}	\overline{LB}^{**}	\overline{UB}^{**}	Mode	I/O Pin		Supply Current
						I/O ₀ ~I/O ₇	I/O ₈ ~I/O ₁₅	
H	X	X*	X	X	Not Select	High-Z	High-Z	I _{SB} , I _{SB1}
L	H	H	X	X	Output Disable	High-Z	High-Z	I _{CC}
L	X	X	H	H		High-Z	High-Z	
L	H	L	L	H	Read	D _{OUT}	High-Z	I _{CC}
			H	L		High-Z	D _{OUT}	
			L	L		D _{OUT}	D _{OUT}	
L	L	X	L	H	Write	D _{IN}	High-Z	I _{CC}
			H	L		High-Z	D _{IN}	
			L	L		D _{IN}	D _{IN}	

*X means don't care




32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Data Retention Characteristics*(T_A=0 to 70°C)

Parameter	Operating V _{CC} (V)	Symbol	Test Condition	Min.	Typ.	Max.	Unit
V _{CC} for Data Retention	2.4V~3.6V	V _{DR}	$\overline{CS} \geq V_{CC} - 0.2V$	2.0	-	3.6	V
	1.65V~2.2V			1.5	-	3.6	
Data Retention Current	2.4V~3.6V	I _{DR}	V _{CC} =2.0V $\overline{CS} \geq V_{CC} - 0.2V$ V _{IN} ≥ V _{CC} - 0.2V or V _{IN} ≤ 0.2V			55	mA
	1.65V~2.2V		V _{CC} =1.5V $\overline{CS} \geq V_{CC} - 0.2V$ V _{IN} ≥ V _{CC} - 0.2V or V _{IN} ≤ 0.2V			55	
Data Retention Set-Up Time		t _{SDR}	See Data Retention Wave form (below)	0			ns
Recovery Time		t _{RDR}		5			ms

Data Retention Wave form





32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Read Cycle*

Parameter	Symbol	10ns		15ns		Unit
		Min	Max	Min	Max	
Read Cycle Time	t _{RC}	10	-	15	-	ns
Address Access Time	t _{AA}	-	10	-	15-	ns
Chip Select to Output	t _{CO}	-	10	-	15	ns
Output Enable to Valid Output	t _{OE}	-	5	-	7	ns
\overline{UB} , \overline{LB} Access Time**	t _{BA}	-	5	-	7	ns
Chip Enable to Low-Z Output	t _{LZ}	3	-	3	-	ns
Output Enable to Low-Z Output	t _{OLZ}	0	-	0	-	ns
\overline{UB} , \overline{LB} Enable to Low-Z Output**	t _{BLZ}	0	-	0	-	ns
Chip Disable to High-Z Output	t _{HZ}	0	5	0	7	ns
Output Disable to High-Z Output	t _{OHZ}	0	5	0	7	ns
\overline{UB} , \overline{LB} Disable to High-Z Output**	t _{BHZ}	0	5	0	7	ns
Output Hold from Address Change	t _{OH}	3	-	3	-	ns
Chip Selection Power Up Time	t _{PU}	0	-	0	-	ns
Chip Selection Power Down Time	t _{PD}	-	10	-	15	ns

*The above parameters are also guaranteed for industrial temperature range.

Write Cycle*

Parameter	Symbol	10ns		15ns		Unit
		Min	Max	Min	Max	
Write Cycle Time	t _{WC}	10	-	15	-	ns
Chip Select to End of Write	t _{CW}	7	-	12	-	ns
Address Set-up Time	t _{AS}	1.5	-	1.5	-	ns
Address Valid to End of Write	t _{AW}	7	-	12	-	ns
Write Pulse Width(\overline{OE} High)	t _{WP}	7	-	12	-	ns
Write Pulse Width(\overline{OE} Low)	t _{WP1}	10	-	15	-	ns
\overline{UB} , \overline{LB} Valid to End of Write**	t _{BW}	7	-	12	-	ns
Write Recovery Time	t _{WR}	1.5	-	1.5	-	ns



32M Async Fast SRAM


CS18FS3216W
CS16FS3216W

Write to Output High-Z	t_{WHZ}	0	5	0	7	ns
Data to Write Time Overlap	t_{DW}	5	-	8	-	ns
Data Hold from Write Time	t_{DH}	0	-	0	-	ns
End of Write to Output Low-Z	t_{OW}	3	-	3	-	ns

*The above parameters are also guaranteed for industrial temperature range.


Timing Diagram

Timing Waveform of Read Cycle (1) (Address Controlled, $\overline{CS} = \overline{OE} = V_{IL}$, $\overline{WE} = V_{IH}$, \overline{UB} , $\overline{LB} = V_{IL}$ **)



** Those parameters are applied for x16 mode only.

Timing Waveform of Read Cycle (2) ($\overline{WE} = V_{IH}$)





32M Async Fast SRAM


CS18FS3216W
CS16FS3216W

NOTES (Read Cycle)

1. \overline{WE} is high for read cycle
2. All read cycle timing is referenced from the last valid address to the first transition address.
3. t_{HZ} and t_{OHZ} are defined as the time at which the outputs achieve the open circuit condition and are not referenced to V_{OH} or V_{OL} levels.
4. At any given temperature and voltage condition, t_{HZ} (Max.) is less than t_{LZ} (Min.) both for a given device and from device to device.
5. Transition is measured $\pm 200\text{mV}$ from steady state voltage with Load (B). This parameter is sampled and not 100% tested.
6. Device is continuously selected with $\overline{CS} = V_{IL}$.
7. Address valid prior to coincident with \overline{CS} transition low.
8. For common I/O applications, minimization or elimination of bus contention conditions is necessary during read and write cycle.

**** Those parameters are applied for x16 mode only.**

Timing Waveform of Write Cycle (1) (\overline{OE} Clock)




**** Those parameters are applied for x16 mode only.**



32M Async Fast SRAM


CS18FS3216W
CS16FS3216W

Timing Waveform of Write Cycle (2) (\overline{OE} = Low fixed)



** Those parameters are applied for x16 mode only.

Timing Waveform of Write Cycle (3) (\overline{CS} = Controlled)




** Those parameters are applied for x16 mode only.



32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Timing Waveform of Write Cycle (4) (\overline{UB} , \overline{LB} Controlled)



NOTES (Write Cycle)

1. All write cycle timing is referenced from the last valid address to the first transition address.
2. A write occurs during the overlap of a low \overline{CS} , \overline{WE} , \overline{LB} and \overline{UB} . A write begins at the latest transition \overline{CS} going low and \overline{WE} going low ;
A write ends at the earliest transition \overline{CS} going high or \overline{WE} going high. t_{WP} is measured from the beginning of write to the end of write.
3. t_{CW} is measured from the later of \overline{CS} going low to end of write.
4. t_{AS} is measured from the address valid to the beginning of write.
5. \overline{WE} is measured from the end of write to the address change. t_{WR} applied in case a write ends as \overline{CS} or \overline{WE} going high.
6. If \overline{OE} , \overline{CS} and \overline{WE} are in the Read Mode during this period, the I/O pins are in the output low-Z state. Inputs of opposite phase of the output must not be applied because bus contention can occur.
7. For common I/O applications, minimization or elimination of bus contention conditions is necessary during read and write cycle.
8. If \overline{CS} goes low simultaneously with \overline{WE} going or after \overline{WE} going low, the outputs remain high impedance state.
9. D_{OUT} is the read data of the new address.
10. When \overline{CS} is low : I/O pins are in the output state. The input signals in the opposite phase leading to the output should not be applied.

** Those parameters are applied for x16 mode only




32M Async Fast SRAM

CS18FS3216W
CS16FS3216W

Package outline dimensions

48ball TFBGA-6x8mm (ball pitch: 0.75mm)



NOTES:

1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS.
2. PIN#1 DOT MARKING BY LASER OR PAD PRINT.
3. SYMBOL "N" IS THE NUMBER OF SOLDER BALLS.
4. TOLERANCES:
 LINEAR : X.X = ±0.1
 X.XX = ±0.05
 X.XXX = ±0.025